


# CRYSTAL BOLLARD PLRE4

# **PRODUCT SHEET**





## **TECHNICAL DESCRIPTION**

Use: Solar outdoor beacon device, no wiring required. Structure: Tempered glass 15 mm thick on aluminium tube.

LED Colours: RGB colours + White 4000 K.

CRI of White LED: Minimum 80.

Luminous Flux: 4 lm.

Battery: LiFePO4 (3.2 V / 4.5 Ah). Solar Panel: SunPower Back Contact. Operating Temperatures: -10°C to +60°C.

Dimensions: 119 x 73 mm.

Weight: 1.25 kg.

Compression Resistance (EN62262 - IK10): 3 tons (suitable for vehicles up to 32 tonnes).

Class III - IP67 - IK10 - CE.



#### **AUTONOMY**

Battery Capacity: 4.5 Ah. Autonomy: 480 hours.

Embedded intelligence enabling optimal battery management based on the plot's environment for operation 365 nights a year.

Estimated battery lifespan: 22 years with 8000 cycles at a depth of discharge not exceeding 55% (equivalent to 8 hours of nightly use in Paris, with 50% daylight sunlight).

#### **CONNECTION**

Bluetooth connection for remote control of the product via the Nowatt Lighting application.

Nowatt Lighting application available on Android and iOS smartphones. The connection is protected by a code.







# **FEATURES**


Device ON/OFF function.

Configuration of lighting scenario among 8 standard scenarios. Configuration of operating duration (for every night):

- Number of hours after sunset.
- Number of hours before sunrise.



### **LIGHTING SCENARIOS**



## **INSTALLATION**

The installation methodology for Crystal bollards depends on the type of ground. Please refer to our manual available upon request.

## **WARRANTY**

"The product is guaranteed for two years in accordance with the warranties of the French Lighting Syndicate."

